

Excelis MPX


HIGH RESOLUTION MICROSCOPY CAMERA

The new *Excelis* MPX-6C CMOS microscopy cameras deliver exceptional performance in a compact, low-profile design.

The revolutionary, feature-rich *CaptaVision+* software provides real-time image stitching, real-time depth-of-field fusion, report generation & export, plus more!



SONY Professional CMOS Sensor



The MPX-6C uses a Sony Starvis® 6MP 1/1.8" CMOS sensor—IMX178, with 2.4 x 2.4µm pixels. With a captured image resolution reaching 3072x2048 pixels, the MPX-6C resolves fine details from low to high magnifications.

Advanced Rolling Shutter Technology

The rolling shutter of the MPX-6C provides very high resolution, excellent light sensitivity in a color camera, and high speed acquisition and read out ideally suited for microscopy imaging especially in brightfield and stereo applications.





USB 3.0 High-Speed Transmission

USB 3.0 super-speed transmission interface is simple, convenient and ensures a stable high-data transmission rate allowing fast-focusing at high resolution. Imaging can be performed at a rate of 40fps at 6MP!



Excellent Color Reproduction

The MPX-5 Pro's core ISP color-interpolation algorithm effectively simulates the human eye's sensitivity to color. The colors in the image are true to the color seen in the eyepiece, whether it is a biological brightfield, stereo or fluorescence image.



Feature-Rich *CaptaVision+* Imaging Software

The innovative interface and workflow-based design redefines the image acquisition → editing → measurement → report output workflow process saving operating time and improving productivity.



- 6MP CMOS Camera
- Ultra-high speed Image Transfer
- USB 3.0 Connectivity
(USB 2.0 Compatible)
- CaptaVision+ Imaging Software




CAMERA & SOFTWARE SPECIFICATIONS

Model	AU-6C-CMOS
Sensor / Model	CMOS • Sony IMX178LQJ-C
Sensor Size	1/1.8"; 0.65x C-mount (recommended)
Image Transmission	High-speed
Pixel Size	2.4µm x 2.4µm
Resolution	3072 (H) X 2048 (V)
Frame Rate	40FPS (3072 X 2048)
Shutter Mode	Rolling
Exposure Time	0.13ms—15s
Automatic Settings	Exposure, Color Scale, White Balance
Manual Settings	Exposure, Gain, Noise Reduction, Gamma, Flat Field Correction
Color Temperature	2000-15000K
ADC Depth	12Bit
Operating Temperature & Humidity	0-60°C
Camera Size & Weight	68x68x46mm / 330g
Data Interface	USB 3.0, compatible with USB 2.0
PC Imaging Software	CaptaVision+ Imaging Software (for PC only; Mac OS not supported) Live/still image measurement and annotation; flat field correction; extended depth of focus (focus stacking); image stitching; fluorescence image settings; fluorescence multi-color channel merge; HDR (High Dynamic Range) function Image Types: JPEG, PNG, and TIFF Supports 4 cameras simultaneously in SDK
System Software Compatibility	Windows 7, 8, and 10 (64 bit) System Requirements: Intel processor (Core i5 or higher); 8GB RAM or more; USB 2.0 Hi-Speed port or higher


Design, features and specifications are subject to change without notice.

CaptaVision+ Features

- Intelligent 12-bit ISP color reproduction
- Real-time depth-of-field fusion
- Real-time image stitching
- Real-time fluorescence image synthesis and editing
- HDR image synthesis
- Micro-imaging-based intelligent automatic exposure
- Intelligent flatfield correction based on dynamic calculation
- Smart measurement workflow
- Implements multiple iterations of workflow execution
- Supports single shot, delayed camera
- Automatic video and delay video generation
- Output format selection
- User parameter group save and load
- Dynamic / static measurement
- Layered measurement
- Customize measuring gauges, layers, precision, image naming, style, save location
- Data export as TXT or Excel
- Drawing tools: points, lines, rectangles, polygons, circles, arcs & angles
- Report generation and printing




Outstanding color reproduction




Real-time depth-of-field fusion




Real-time stitching can generate mosaic images while moving the stage



300x240 pixels, RGB:281K



Advanced noise reduction for fluorescence imaging



Innovative interface streamlines the image acquisition / editing / measurement & report output workflow process

ISO 9001

Design and production adheres to ISO9001 international quality standard.

ISO 14001

Design and production meets the requirements of international standard ISO 14001 for environmental management.

